BulletCam HL (5 Mp/4 mm)

Wired Al-powered security IP camera with a 85° viewing angle, hybrid illumination, TrueWDR, microphone, and PoE/12 V. For outdoor and indoor use.

Camera

Image sensor

5 MP CMOS, 1/2.8" type

Lens focal length

4 mm

Maximum aperture

f/1.6

Lens iris type

fixed

Lens focal type

fixed

Field of view

horizontal: 85° vertical: 46° diagonal: 110°

Maximum illumination distance

white LED: up to 50 mIR LED: up to 50 m

• white LED: up to 164 ft

• IR LED: up to 164 ft

Intelligent lighting control automatically adjusts the intensity of IR and white LEDs in real time to prevent overexposure. This ensures clear visibility of objects at varying distances — whether close to or far from the camera — in low-light conditions.

	Desclution
v. i	Resolution
Video	• 5 MP (2880 × 1620)
	• 4 MP (2560 × 1440)
	• 3 MP (2304 × 1296)
	• 2 MP (1920 × 1080)
	• 0.6 MP (1024 × 576)
	Frame rate
	up to 25 fps
	Image rotation
	0°, 180°
	Video codec
	H.265, H.264
	Dynamic range
	True WDR
	Storage
	microSD
	complete set.
	Built-in microphone
Audio	With the corresponding settings, the camera can record audio at the
	scene.
	Audio codec
	G711-ULAW, G711-ALAW, G726, G722
	Motion detection
Intelligent video analytics	The camera detects motion using software image frame analysis.
	Al object detection
	People
	Pets
	reis
	Built-in microphone With the corresponding settings, the camera can record audio at the scene. Audio codec G711-ULAW, G711-ALAW, G726, G722 Motion detection The camera detects motion using software image frame analysis. Al object detection People

·	
	Port
Network	1 × RJ-45 self-adaptive Ethernet (10/100 Mbps)
	Protocol
	HTTP, HTTPS, TCP/IP, IPv4, IPv6, SNMP, RTSP, UDP, DHCP, DNS,
	DDNS
	Interoperability
	ONVIF (Profile S/T*)
	Ajax cameras and NVRs can be integrated into third-party video management systems (VMS).
	* Profile T is supported for basic streaming and configuration.
	Advanced features such as metadata, event handling, or edge
	recording may be unavailable.
	<u>Learn more</u>
	Video protocol
Key features	JetSparrow
	Fast and encrypted peer-to-peer video protocol developed by Ajax
	Systems.
	Viewal waifi ation of Airm alarma
	Visual verification of Ajax alarms The system allows you to configure a scenario according to which
	Ajax detectors trigger selected cameras to start recording. The
	recorded event is immediately delivered to the mobile or desktop
	monitoring app.
	Privacy
	Advanced privacy controls ensure a high level of personal data protection. All access rights — including those for mobile app users,
	installers, and monitoring company operators via Ajax PRO Desktop
	— are fully configurable by the device owner. This guarantees that
	only authorized parties can access video streams, event history, or
	device settings, in accordance with the owner's preferences.
	mTLS
Sabotage protection	Encrypted connection for data protection.
	Authentication
	via Ajax Cloud
	Secure Boot
	Protection against firmware spoofing.
	OTA signature verification

Secure automatic firmware update.

Power supply	PoE standard 802.3at/af
	PoE power consumption • maximum: up to 7.3 W • average: up to 6.0 W
	Power supply unit 12 V- ± 20%, 1 A
	12 V DC power consumption • maximum: up to 6.2 W • average: up to 5.1 W
Enclosure	Dimensions 198 × 76 × 76 mm 7.78" × 2.99" × 2.99"
	Weight 550 g 1.21 lb
	Operating temperature range from -30 °C to +60 °C from -22 °F to 140 °F
	Operating humidity up to 90%
	Protection class IP65
Color	Black White
Complete set	BulletCam HL (5 Mp/4 mm) Installation template Installation kit Quick start guide
Warranty	24 months