## MORLEY-IAS LITE ADDRESSABLE FACP SUPPORTING UP TO 32 DEVICES



LT-159 control panels include Honeywell's Advanced protocol which maximizes the speed and efficiency of alarm detection, as well as providing maximum information to the installer.

The 4.3" (480x272 pixel) Touch Screen provides an intuitive user interface via its menus with quick and easy system operation. The LT-159 Series control panels allow configuration from the screen itself and a maximum of 159 addressable devices in the system.

## PART. NO

LT-159

## **FEATURES**

- Includes 6 AA-size 2,800mAh nickel metal hydride (Ni-MH) batteries
- Language selection, available in English, Italian, Spanish Arabic, Portuguese, Romanian, Dutch, French, Turkish, Albanian, Slovenian, Serbian, Croatian, Greek, Bulgarian, German
- Quick configuration of the unit from the same display
- 2x Serial Communication port
- Certified to EN54-2:1997+A1:2006 and EN54-4:1997+A1:2002 and A2:2006; LVD 62.368-1:2014+A11

## TECHNICAL SPECIFICATION

MAIN POWER SUPPLY	230 V AC +/- 15%, 50 / 60 Hz	DIMENSIONS (HXWXD)	126.9 x 206.9 x 42.7 mm
POWER CONSUMPTION	max. 24W	OPERATING TEMPERATURE	0°C to +40°C
BATTERY CAPACITY	6x AA size 2.800 mAh	HUMIDITY	5% - 95% non-condensing
OUTPUTS	1 fault (NO/NC); 1 alarm (NO/NC)	WEIGHT	400 g
SOUNDER OUTPUT	1, max. 50 mA	PROTECTION CLASS	IP30
COLOR	RAL 7021/9005		

